

NEOREST NX1 Dual Flush Toilet, 1.0 GPF / 0.8 GPF

FEATURES

- Sleek, low profile one-piece skirted Smart Bidet Toilet with integrated personal cleansing and comfort features
- Ultra high-efficiency dual flush functionality - 1.0 GPF / 0.8 GPF (3.8 LPF / 3.0 LPF)
- TORNADO FLUSH® System utilizes 360° cleaning power to reach every part of the hole-free rim design bowl
- Auto flush - with back-up manual flush for power outages
- Auto open/close lid
- PREMIST® automatically mists the bowl before each use
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Gentle aerated, warm water, dual-action spray with oscillating and pulsating features
- Instantaneous water heater for continuous warm water and energy savings
- Adjustable spray position, water temperature, and water pressure
- EWATER+® auto-cleans wand, bowl, and under-seat after every use
- Heated seat with temperature control
- Seamless seat design eliminates the gap where dirt collects
- Warm air dryer with five variable temperature settings
- Automatic air deodorizer
- Automatic and programmable energy saving systems
- Multifunction ergonomic stick-style remote control
- 4-users' personalized memory settings
- Universal Height, ADA compliant
- Night light

COMPONENTS

- MS902CUMFG

COLORS/FINISHES

- #01 Cotton

PRODUCT SPECIFICATION

The NEOREST NX1 with the TORNADO FLUSH system toilet shall be 1.0 GPF / 0.8 GPF (3.8 LPF / 3.0 LPF). Toilet shall have CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall be of skirted design, elongated front bowl with auto open and close lid. Toilet shall be TOTO Model MS902CUMFG#01.



1G ONE GALLON PER FLUSH

EWATER+

U UNIVERSAL HEIGHT

CEFIONTECT

TORNADO FLUSH

CODES/STANDARDS

- Meets and exceeds ASME A112.4.2, ASME A112.19.2/CSA B45.1, ASME A112.18.1/CSA B125.1, UL 1431, CSA C22.2 # 68
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, and others
- ADA Compliant
- Complies with CA Prop 65 warning requirements



CALGreen

MS902CUMFG

NEOREST NX1 Dual Flush Toilet, 1.0 GPF / 0.8 GPF

SPECIFICATIONS

Water Use	1.0 GPF / 0.8 GPF (3.8 LPF / 3.0 LPF)
Flush System	TORNADO FLUSH
Water Pressure	Min: 7.25 PSI (0.05MPa) Flowing Max: 108.75 PSI (0.75MPa) Static
Water Surface	8-1/2" x 7-1/2"
Trap Diameter	2" (51 mm)
Trap Seal	2-1/8" (54 mm)
Warranty	Three Year Limited (Residential) One Year Limited (Commercial)
Material	Bowl: Vitreous China Seat + Cover: Plastic
Power Rating	AC 120 V, 60 Hz, 1290 W
Power Cord	3.9 ft (1.2m)
Rear Washing	Approx. 0.08 - 0.11 gal/min
Soft Washing	Approx. 0.08 - 0.11 gal/min
Front Washing	Approx. 0.08 - 0.11 gal/min
Wide Front Washing	Approx. 0.09 - 0.11 gal/min
Washing Spray Temperature	Approx. 86°F - 104°F (30°C - 40°C)
Safety Feature	Temperature Fuse
Drying Feature	Air Temperature: Approx. 95°F - 140°F (35°C - 60°C)
Airflow Volume	8.83 ft ³ /min
Dryer Safety Feature	Temperature Fuse
Seat Warming Feature	Surface Temperature: Approx. 82°F - 97°F (28°C - 36°C)
Seat Heater Capacity	540 W
Air Purifying Feature	O2 Deodorizer
Air Volume	5.65 ft ³ /min
Ambient Temperature Range	32°F - 104°F (0°C - 40°C)
Product Size	31-1/2" L x 18-3/8" W x 23" H
Product Weight	141 lbs
Floor to Seat Height	17-5/16" (440mm)
Shipping Weight	MS902CUMFG: 161 lbs
Shipping Dimensions	MS902CUMFG: 36-3/4" L x 21-1/2" W x 31-5/8" H

INSTALLATION NOTES

- For use with potable water only. Do not use with recycled water.
- Warning: If there is a base board in the restroom, the center of the floor drain should be a minimum of 12" from the base board.
- It is highly recommended to use a surge protector to prevent damage in the event of a power surge.

